



Product Description & Technical Specifications for World Class Patch Binder

PRODUCT DESCRIPTION

WORLD CLASS TEXTURED PATCH BINDER is a Polymeric concrete modifier developed for the purpose of patching low areas (bird baths) on Portland Cement Tennis Courts. When WORLD CLASS PATCH BINDER is mixed with Portland Cement and sand, it increases the strength of the cement patch and promotes adhesion to both existing cement and the WORLD CLASS SURFACE SYSTEMS. WORLD CLASS PATCH BINDER may also be used as a concrete slurry to be applied over UNSURFACED PORTLAND CEMENT PAVEMENTS. All patched or slurried areas should be etched with an acid solution and washed clean.

WORLD CLASS PATCH BINDER formulations contain NO VINYL ACRYLICS, NO ETHYLENE GLYCOLS, NO ASPHALTIC EMULSIONS, NO ASBESTOS and NO MERCURY.

TECHNICAL SPECIFICATIONS FOR WORLD CLASS PATCH BINDER

% Solids:	47%
Dilution for Patch Binder:	Mixed 100 pounds of Silica Sand with two gallons of (sifted) Portland Cement. Add undiluted WORLD CLASS PATCH BINDER until desired consistency is achieved. Before patching bird bath areas, prime the areas with one part WORLD CLASS PATCH BINDER and two parts water. Larger sand may be used in deeper patches, but smaller sand (the size used in the color coating) should be used near the top of the patch.
Dilution for Slurry Coat:	Mix 200 pounds of Silica Sand with one bag of Portland Cement. Add 2 1/2 gallons of WORLD CLASS PATCH BINDER and five gallons of water. MIX WELL! Should be applied in cool temperatures or court should be misted with water. Coverage of this mix is approximately 1600 to 1800 square feet.
Packaging:	Five, thirty and fifty-five gallon containers