



# Product Description & Technical Specifications for World Class Acrylic Resurfacer

## PRODUCT DESCRIPTION

WORLD CLASS ACRYLIC RESURFACER concentrate is a high solids 100% acrylic material designed for asphalt and concrete pavements. WORLD CLASS ACRYLIC RESURFACER is to be mixed with silica sand and water at the job site. It may be used to correct minor bird baths, fill voids and blemishes in pavements, and to re-establish consistent texture prior to applying WORLD CLASS COLOR COATING SYSTEMS.

WORLD CLASS ACRYLIC RESURFACER formulations contain NO VINYL ACRYLICS, NO ETHYLENE GLYCOLS, NO ASPHALTIC EMULSIONS, NO ASBESTOS and NO MERCURY.

## TECHNICAL SPECIFICATIONS FOR WORLD CLASS ACRYLIC RESURFACER

<b>Pigments:</b>		27.23%
Black Iron Oxide	4%	
Silica & Extenders	23.23%	
<b>Vehicle:</b>		72.77%
Acrylic Emulsion	37%	
Minor Additives	1.2%	
Volatiles (including water)	34.57%	
<b>TOTAL:</b>		100%
Weight by gallon:	10 pounds	
% Solids by Weight:	63%	
% Acrylic:	37%	
Rate of Application:	.04 - .06 undiluted gallons per square yard	
Mixing:	18 gallons Acrylic Resurfacer, 12 gallons of water and 150 - 200 pounds Silica Sand	
Packaging:	Thirty and fifty-five gallon containers	
Colors:	Dark Gray	