



# Product Description & Technical Specifications for World Class Patch & Level

**PRODUCT DESCRIPTION**

WORLD CLASS PATCH & LEVEL is a high solids 100% Acrylic material. WORLD CLASS PATCH & LEVEL is designed for the leveling of bird baths (depressions), gouges, and minor cracks on asphalt or concrete pavements. WORLD CLASS PATCH & LEVEL is to be used undiluted and may be used over and over, simply place the lid back on the container. Deep patches should be filled in multiple layers, not exceeding 1/4" in depth. WORLD CLASS PATCH & LEVEL should be allowed to dry a minimum of 24 hours before coating with WORLD CLASS SURFACING SYSTEMS.

WORLD CLASS PATCH & LEVEL formulations contain NO VINYL ACRYLICS, NO ETHYLENE GLYCOLS, NO ASPHALTIC EMULSIONS, NO ASBESTOS and NO MERCURY.

**TECHNICAL SPECIFICATIONS FOR  
WORLD CLASS PATCH & LEVEL**

<b>Pigments:</b>		72%
Color Pigments	1%	
Silica	71%	
<b>Vehicle:</b>		28%
Acrylic Emulsion	28%	
<b>TOTAL:</b>		100%
Weight by gallon:	15.6 pounds	
% Solids by Weight:	90%	
% Acrylic:	20%	
Dilution:	Use undiluted	
Packaging:	Five, thirty and fifty-five gallon containers	
Colors:	Green, Red & Neutral	