



Product Description & Technical Specifications for World Class Color Concentrate

PRODUCT DESCRIPTION

WORLD CLASS COLOR CONCENTRATE is the highest pigmented, 100% acrylic color coating system designed specifically for asphalt and concrete surfaces. WORLD CLASS COLOR CONCENTRATE may be used for textured coats and topcoats. For texture coats, simply dilute color concentrate with water and silica sand. The speed of play and ball bounce can easily be adjusted by varying the size and the amount of silica sand to the concentrate. To provide a protective, in-depth color topcoat, simply add water to the color concentrate.

WORLD CLASS COLOR CONCENTRATE formulations contain NO VINYL ACRYLICS, NO ETHYLENE GLYCOLS, NO ASPHALTIC EMULSIONS, NO ASBESTOS and NO MERCURY.

TECHNICAL SPECIFICATIONS FOR DARK GREEN COLOR CONCENTRATE

Pigments:		23.64%
Chromium Oxide Green	7.04%	
Silica & Extenders	16.60%	
Vehicle:		76.36%
Acrylic Emulsion	28.51%	
Minor Additives	1.9%	
Volatiles (including water)	45.95%	
TOTAL:		100%

Weight by gallon: 10 pounds

% Solids by Weight: 44%

% Acrylic: 25.9%

Rate of Application: .03 - .06 gallons per square yard

Dilution: A. Texture coats - 2 part concentrate, one part water and one part sand

B. Topcoat - Equal parts concentrate and water

Packaging: Thirty and fifty-five gallon containers

Colors: Dark Green, Medium Green, Light Green, Brick, Chocolate, Maroon, Coral, Delta Blue, Khaki