



Product Description & Technical Specifications for World Class Acrylic Crack Filler

PRODUCT DESCRIPTION

WORLD CLASS ACRYLIC CRACK FILLER is a blend of three Acrylic Emulsions mixed with selected Silica. Each Acrylic Resin was selected to provide special properties — one for adherence and durability — one for elasticity and low shrinkage — and one for moisture deterrence. WORLD CLASS ACRYLIC CRACK FILLER is to be used undiluted and may be used over and over, simply place the lid back on the container.

WORLD CLASS ACRYLIC CRACK FILLER formulations contain NO VINYL ACRYLICS, NO ETHYLENE GLYCOLS, NO ASPHALTIC EMULSIONS, NO ASBESTOS and NO MERCURY.

TECHNICAL SPECIFICATIONS FOR WORLD CLASS ACRYLIC CRACK FILLER

Pigments:		80%
Color Pigments	1.5%	
Silica	78.5%	
Vehicle:		20%
Acrylic Emulsion	20%	
TOTAL:		100%
Weight by gallon:	13 pounds	
% Solids by Weight:	90%	
% Acrylic:	14%	
Rate of Application:	Approximately 300 linear feet of half inch cracks per gallon; use undiluted	
Packaging:	One and five gallon containers	
Colors:	Green, Red & Neutral	